

## READING LAMP ASHA

### Designer

Itamar Burstein

### Description

A first LED module located at the cylindrical end of the lampshade and protected by a PMMA diffuser, illuminates upwards: power 3W colour temperature 3000 K (warm white) 330 lumens. A second LED module located at the conical end of the lampshade and protected by a PMMA diffuser, illuminates downwards: power 7W colour temperature 3000 K (warm white) 770 lumens. Possibility of varying the intensity of each LED module independently thanks to two switch/dimmer buttons located on the side of the lampshade. Brief touch : ON /OFF. Continuous touch : dimmer - variation of the intensity. Black PVC electric cable.

### Technical characteristics

A first LED module located at the cylindrical end of the lampshade and protected by a PMMA diffuser, illuminates upwards: power 3W colour temperature 3000 K (warm white) 330 lumens. A second LED module located at the conical end of the lampshade and protected by a PMMA diffuser, illuminates downwards: power 7W colour temperature 3000 K (warm white) 770 lumens. Possibility of varying the intensity of each LED module independently thanks to two switch/dimmer buttons located on the



### DIMENSIONS

Height 1,610 mm | Diameter 200 mm | Weight 4 kg

side of the lampshade. Brief touch : ON /OFF. Continuous touch : dimmer - variation of the intensity. Black PVC electric cable. A first LED module located at the cylindrical end of the lampshade and protected by a PMMA diffuser, illuminates upwards: power 3W colour temperature 3000 K (warm white) 330 lumens. A second LED module located at the conical end of the lampshade and protected by a PMMA diffuser, illuminates downwards: power 7W colour temperature 3000 K (warm white) 770 lumens. Possibility of varying the intensity of each LED module independently thanks to two switch/dimmer buttons located on the side of the lampshade. Brief touch : ON /OFF. Continuous touch : dimmer - variation of the intensity. Black PVC electric cable. A first LED module located at the cylindrical end of the lampshade and protected by a PMMA diffuser, illuminates upwards: power 3W colour temperature 3000 K (warm white) 330 lumens. A second LED module located at the conical end of the lampshade and protected by a PMMA diffuser, illuminates downwards: power 7W colour temperature 3000 K (warm white) 770 lumens. Possibility of varying the intensity of each LED module independently thanks to two switch/dimmer buttons located on the side of the lampshade. Brief touch : ON /OFF. Continuous touch : dimmer - variation of the intensity. Black PVC electric cable.

## **More information on**

[www.cinna.fr](http://www.cinna.fr)

© Ligne Roset 2024